

Technical Data

Engineered 3-ply door frames

Wood species	Nordic Spruce, Spruce knot-free, Nordic Pine, Siberian Larch, Larch knot-free, Reclaimed Spruce, Aged Spruce, Ash, Oak, Beech, Hard Maple	
Lengths	2150 mm, shorter lengths upon request (hardwood 2050 mm)	
Widths	Spruce	145 / 160 / 250 mm
	Pine	145 mm
	Larch	145 / 160 / 250 mm
	Reclaimed Spruce	145 / 160 mm
	Aged Spruce	145 / 160 / 250 mm
	Hardwood	145 mm
Thickness	42 mm Special thicknesses possible when purchased by pallets.	
Grades	Softwood:	A/A knotty Pine and Larch also A/A knot-free
	Hardwood:	A/A knot-free
Edge finishing	min. 18 mm free of knots and defetcs	
Gluing	A 100, AW 100 on request, according to Austrian Standards (Ö-Norm) B8003 and B8024, EN 13353, E1	
Thickness of top layers	Softwood:	5,3 mm
	Hardwood:	4,0 mm
Centre layers	in the respective species of wood	
Packet size	145 mm wide = 161 pieces 160 mm wide = 138 pieces 250 mm wide = 92 pieces	

